

QAMAR FD21HN

Linear Low Density Polyethylene

SPDC Ltd.

PROSPECTOR®

www.ulprospector.com

Technical Data

Product Description

QAMAR FD21HN is a Linear Low Density Polyethylene material. It is available in Africa & Middle East, Asia Pacific, Europe, or North America for blown film.

Important attributes of QAMAR FD21HN are:

- Antiblock
- Clarity
- Slip

Typical application of QAMAR FD21HN: Film

General

Material Status	• Commercial: Active
Literature ¹	• Technical Datasheet (English)
Availability	• Africa & Middle East • Asia Pacific • Europe • North America
Additive	• Antiblock • Slip
Features	• Antiblocking • General Purpose • Medium Clarity • Slip
Uses	• Film • General Purpose
Processing Method	• Blown Film

Physical	Nominal Value (English)	Nominal Value (SI)	Test Method
Density	0.918 g/cm ³	0.918 g/cm ³	ASTM D4883
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0 g/10 min	2.0 g/10 min	ISO 1872-2

Mechanical	Nominal Value (English)	Nominal Value (SI)	Test Method
Tensile Stress (Yield)	1310 psi	9.00 MPa	ISO 1872-2
Tensile Strain (Break)	> 430 %	> 430 %	ISO 1872-2
Flexural Modulus	29000 psi	200 MPa	ISO 1872-2

Films	Nominal Value (English)	Nominal Value (SI)	Test Method
Film Thickness - Tested	1.2 mil	30 µm	
Tensile Modulus			ISO 527-3
MD : 1.2 mil (30 µm)	27600 psi	190 MPa	
TD : 1.2 mil (30 µm)	30500 psi	210 MPa	
Tensile Stress			ISO 527-3
MD : Break, 1.2 mil (30 µm)	5800 psi	40.0 MPa	
TD : Break, 1.2 mil (30 µm)	5080 psi	35.0 MPa	
Tensile Elongation			ISO 527-3
MD : Break, 1.2 mil (30 µm)	600 %	600 %	
TD : Break, 1.2 mil (30 µm)	900 %	900 %	
Dart Drop Impact (1.2 mil (30 µm))	110 g	110 g	ISO 7765-1
Elmendorf Tear Strength			ISO 6383-2
MD : 1.2 mil (30 µm)	6.7 lbf	30 N	
TD : 1.2 mil (30 µm)	31 lbf	140 N	

Hardness	Nominal Value (English)	Nominal Value (SI)	Test Method
Shore Hardness (Shore D)	54	54	ISO 868

Thermal	Nominal Value (English)	Nominal Value (SI)	Test Method
Brittleness Temperature	< -94.0 °F	< -70.0 °C	ISO 974
Vicat Softening Temperature	212 °F	100 °C	ISO 306
Melting Temperature	252 °F	122 °C	ISO 11357-3

Optical	Nominal Value (English)	Nominal Value (SI)	Test Method
Haze (1.18 mil (30.0 µm))	14 %	14 %	ISO 14782



Extrusion	Nominal Value (English)	Nominal Value (SI)
Screw L/D Ratio	24.0:1.0	24.0:1.0

Extrusion Notes

Resin Temperature: 180°C
Blow Up Ratio: 2.0
Extruder: 40mm, L/D=24
Die Diameter: 75 mm

Notes

¹ These links provide you with access to supplier literature. We work hard to keep them up to date; however you may find the most current literature from the supplier.

² Typical properties: these are not to be construed as specifications.



Where to Buy

Supplier

SPDC Ltd.
, Japan
Web: <http://www.spdc.co.jp/>

Distributor

Please contact the supplier to find a distributor for QAMAR FD21HN

