



**PRODUCTS**

PVC Suspension Resin

[SG580](#)

[SG660](#)

[SP660](#)

[SG710](#)

[Others](#)

[Research & Development](#)

[Home](#) / [Products](#) / [PVC Suspension Resin...](#)

# SG660



Our PVC general purpose resins are produced by suspension polymerization process, white powder and free-flowing resins, blended with other additives by using standard mixing techniques. They are developed to serve a wide range of usage especially for general purpose product

Property	Test method	Unit	Specification
K - Value	DIN 53726	-	65 - 67
Apparent Bulk Density	ISO 60	g/ml	0.53 - 0.59
Volatile Matter	ASTM D 3030 - 95	%	0.3 max
Sieve Analysis	ASTM D 1921 - 96		
Retained on 250 micron		%	2.0 max
Retained on 75 micron		%	90.0 min

**ABOUT US**

[Company profile](#)  
[Vision / Mission](#)  
[Awards & Standards](#)

**SUSTAINABILITY DEVELOPMENT**

[Sustainability Development](#)  
[Sustainability Management](#)  
[Social Activities](#)  
[Environmental Management](#)  
[Health & Safety](#)

**PRODUCTS**

[PVC Suspension Resin](#)  
[Others](#)  
[Research & Development](#)

**NEWS**

[Company News](#)  
[Press Release](#)  
[Photo Gallery](#)  
[Video Clips](#)

**SUPPORT**

[FAQs](#)  
[Download Center](#)  
[Technical Service](#)

**CONTACT**

[Company Information](#)  
[Career](#)